


M12 Solenoid valve special junction box

8-port, With pluggable terminal

8M12-2PF-J/F




- M12, 8-channel single signal
- Protection class IP65
- External solenoid valve signal
- With pluggable terminal.
- With on-site diagnosis function

Technical parameter


Electrical parameter

Rated voltage	10...30VDC
Rated current	10A
Current	2 A per signal contact
The LED working current	10mA per channel
Ambient temperature range	-30...80°C
Screw-in thread	PG13.5
I/O port	M12 x 1
Number of Pins	3
Display operating voltage	LED, green
Display switching state	LED, yellow
Housing material	Black Nylon
Contacts	Brass, Gold-plated
Seal	Viton (FPM)
Protection class	IP65, (screwed together)

Pluggable Terminal



Wiring diagram



8-port,single signal

PIN	J1-3	J1-4
Terminal	18	1
PIN	J2-3	J2-4
Terminal	18	2
PIN	J2-3	J2-4
Terminal	18	3
PIN	J4-3	J4-4
Terminal	18	4
PIN	J5-3	J5-4
Terminal	18	5
PIN	J6-3	J6-4
Terminal	18	6
PIN	J7-3	J7-4
Terminal	18	7
PIN	J8-3	J8-4
Terminal	18	8